PATENTS - TRADE MARKS - DESIGNS

PatentOffice

1562

Discovery House, Phillip ACT 2606
PO Box 200, Woden ACT 2606
Australia
Phone +61 -2 6283 2211
Facsimile +61 -2 6285 3593
Internet http://www.ipaustralia.gov.au

© <u>(7)</u>		SHOW 25.02.80 *J5 6120-562	A(12-R1) E(10-A9B4) L(2-D3)	8091
370	Lightweight concrete prodn. from foamed cament - using ammonium dodecyl benzene sulphonaie foaming agent	mmonium		
Hand For San	In production of light wt. concrete from a foamed cement slurry comprising H ₂ O, foaming agent and cement material, the improvement comprises using as the foaming agent ammonium alkyl aryl sulphonate e.g. ammonium dodecylbenzene sulphonate etc., so that the light wt. concrete exhibits decreased water-absorbability and water-permeability as well as exhibits excellent anti-freezing and-fusing properties without any damage on its fine uniform foamability and variable bulk density. In the ammonium alkylarylsulphonate, the alkyl radical is straight-chained and has 8-18 carbon atoms, and the aryl radical is e.g. phenyl radical etc. The amt. of the alkylarylsulphonate to be added is at least 0.01 wt. part against 100 wt. parts of the cement material in the case of ammonium dodecylbenzenesulphonate. If necsengary a viscosifier such as a water-soluble cellulose deriverge methyl cellulose, ethyl cellulose, methylethyl cellulose, hydroxy ethyl cellulose and CMC etc. may be added.	cement material, agent am- ecylbenz- exhibits bility as f propert- illity and sulphon- 8-18 car- ical etc. at least naterial te. If nec- allose deriv cellulose,		
	(4ppW34).	-	- !	J56120